

FREQUENCY [MHz]	MEASURED TX FREQ	
	MODE	
	CWU	CWL
1.8100	N/A	N/A
3.51000	3.5108	3.5092
5.32000	5.3208	5.3190
7.01000	7.0108	7.0092
10.11000	10.1108	10.1092
14.01000	14.0108	14.0092
18.07000	18.0709	18.0693
21.01000	21.0109	21.0093
24.90000	24.9009	24.8993
28.01000	28.0109	28.0093

SENSITIVITY			
MODE: USB			SINAD 10dB
BAND	FREQ GEN	RX FREQ	dBm
1.8	1.8130	1.811.99	-112.1
3.5	3.5210	3.519.97	-114.1
5.3	5.3530	5.351.97	-115
7.0	7.1510	7.149.96	-115.6
10.0	10.1110	10.109.95	-113.8
14.0	14.2010	14.199.93	-113.2
18.0	18.0810	18.079.91	-111.3
21.0	21.1010	21.099.90	-110.4
24.9	24.9110	24.909.89	-110.2
28.0	28.2110	28.209.88	-108.9

ATTENUATION

20.00

Harmonics				1.		2.		3.		4.		5.		6.		7.		8.		9.	
BAND	SET FREQ	dBm	Watts	FREQ	dBm	FREQ	dBm	FREQ	dBm	FREQ	dBm	FREQ	dBm	FREQ	dBm	FREQ	dBm	FREQ	dBm	FREQ	dBm
1.8	1.810	18.11	6.47	3.6220	-10.95	5.4330	13.70	7.2430	-27.82	9.0540	-22.41	12.6760	-24.40	16.2970	-23.32	19.9190	-28.65	23.5410	-24.91	30.8000	-26.79
3.5	3.510	19.54	8.99	7.0180	-32.96	10.5270	-21.84	17.5460	-22.28	24.5650	-21.71	31.5830	-20.73	38.6010	-21.36	45.6200	-33.61				
5.3	5.320	17.62	5.78	15.6930	-21.29	26.6040	-21.44	37.2460	-19.54	47.8870	-31.42										
7.0	7.010	18.52	7.11	14.0186	-35.34	21.0280	-20.52	28.0370	-36.20	35.0460	-18.73	49.0650	-28.14								
10.0	10.110	16.74	4.72	30.3330	-16.44	50.5540	-25.26														
14.0	14.010	15.90	3.89	28.0220	-35.10	42.0330	-25.43	70.0545	-39.32												
18.0	18.070	13.27	2.12	36.1420	-39.70	54.2130	-29.92														
21.0	21.010	12.42	1.75	42.0186	-34.22	63.0280	-43.45														
24.9	24.900	10.94	1.24	49.8020	-45.59	74.7030	-46.52														
28.0	28.010	10.54	1.13	16.0150	-43.18	56.0218	-51.87														

